



Office de la Propriété
Intellectuelle
du Canada

Un organisme
d'Industrie Canada

Canadian
Intellectual Property
Office

An agency of
Industry Canada

CA 2527467 A1 2006/05/23

(21) **2 527 467**

(12) **DEMANDE DE BREVET CANADIEN
CANADIAN PATENT APPLICATION**

(13) **A1**

(22) Date de dépôt/Filing Date: 2005/11/22

(41) Mise à la disp. pub./Open to Public Insp.: 2006/05/23

(30) Priorités/Priorities: 2004/11/23 (US60/630,390);
2005/11/15 (US11/274,685)

(51) Cl.Int./Int.Cl. **E04B 1/70** (2006.01),
E04B 2/28 (2006.01)


(71) Demandeur/Applicant:
BENJAMIN OBDYKE INCORPORATED, US

(72) Inventeurs/Inventors:
EHRMAN, GEOFFREY N., US;
COULTON, MICHAEL S., US;
RANDELLO, NATHAN L., US

(74) Agent: FINLAYSON & SINGLEHURST

(54) Titre : MUR CREUX DE MACONNERIE ET METHODE DE CONSTRUCTION

(54) Title: MASONRY CAVITY WALL AND METHOD OF ASSEMBLY



(57) Abrégé/Abstract:

A mortar and debris collection device for use within a cavity wall to prevent the blockage of weep holes at the base of the wall. The cavity wall assembly includes a masonry wall, an adjacent inner wall, a wall cavity therebetween, and a free-standing elongate strip of openwork material located within the cavity forming a debris collection surface a spaced distance above a base surface of the cavity. Preferably, the openwork material is inserted and positioned within the cavity after the inner wall and only a base portion of the outer masonry wall is constructed. Thereafter, the upper portion of the outer masonry wall is constructed and any mortar or debris falling into the cavity is caught and supported on the debris collection surface.

Canada

<http://opic.gc.ca> • Ottawa-Hull K1A 0C9 • <http://cipo.gc.ca>

OPIC • CIPU 191

OPIC



CIPU

**MASONRY CAVITY WALL
AND METHOD OF ASSEMBLY**

ABSTRACT OF THE INVENTION

- 5 A mortar and debris collection device for use within a cavity wall to prevent the blockage of weep holes at the base of the wall. The cavity wall assembly includes a masonry wall, an adjacent inner wall, a wall cavity therebetween, and a free-standing elongate strip of openwork material located within the cavity forming a debris collection surface a spaced distance above a base surface of the cavity.
- 10 Preferably, the openwork material is inserted and positioned within the cavity after the inner wall and only a base portion of the outer masonry wall is constructed. Thereafter, the upper portion of the outer masonry wall is constructed and any mortar or debris falling into the cavity is caught and supported on the debris collection surface.

MASONRY CAVITY WALL AND METHOD OF ASSEMBLY

5 BACKGROUND OF THE INVENTION

The present invention relates to a mortar and debris collection device for use within a cavity wall to prevent the blockage of weep holes at the base of the wall, and more particularly, the present invention relates to a masonry cavity wall assembly including a mortar and debris blocker and to a method of assembling a masonry cavity
10 wall with a mortar and debris blocker.

Masonry cavity wall constructions include inner and outer vertical walls with a space or cavity existing therebetween. The inner wall can be made of a wood sheathing or like material, and the outer wall can be made of bricks, stones, blocks or the like held together by mortar. Weep holes are typically located at the base of the
15 outer wall to permit water to drain from the cavity and to permit the cavity to be ventilated to prevent moisture from accumulating therein.

Excess mortar and other building construction debris often falls within the cavity between the inner and outer walls during construction of the cavity wall. The excess mortar and debris drops to the base of the cavity where it can block weep
20 holes. Thus, some masonry cavity walls have been constructed with mortar and debris collection devices, or so-called "blockers".

Examples of such blockers are provided by U.S. Patent Nos.: 6,684,579 B2 issued to Brunson et al; 6,023,892, Re.36,676, and 5,230,189 issued to Sourlis; 5,692,348 issued to Ambrosino; 6,256,955 issued to Lolley; 5,598,673 issued to
25 Atkins; and 5,860,259 issued to Laska, and U.S. Patent Application Nos. 2004/0003558 A1 and 2003/0230035 A1 issued to Collins et al..

While the masonry cavity wall assemblies having mortar and debris blockers and methods of assembling cavity walls disclosed in the above referenced patents may be satisfactory, there continues to be a need for alternatives with respect to the design
30 of such blockers and methods of installation. For instance, the mortar and debris blocker should be capable of being properly installed in a manner requiring only a

minium of skill, effort and time. In addition, the blocker should be capable of efficient manufacture from inexpensive materials and should be of a form permitting efficient storage and shipping.

5 BRIEF SUMMARY OF THE INVENTION

More specifically, the present invention provides a method of assembling a cavity wall with a debris blocker. A base section of a masonry wall is assembled adjacent an inner wall such that a wall cavity is defined therebetween, and a continuous, elongate strip of material is inserted within the wall cavity such that the strip of material is supported on a bottom surface of the wall cavity and forms a debris collection surface a spaced distance above the bottom surface of the wall cavity. The strip of material is an openwork material that permits moisture to drain therethrough and prevents mortar from passing therethrough. After the strip of material is inserted in the cavity, the assembly of an upper section of the masonry wall is completed. Any excess mortar falling into the cavity during the assembly of the upper section of the masonry wall engages and is supported on the debris collection surface and is thereby prevented from blocking weep holes at the bottom of the cavity.

Preferably, the step of inserting the strip of material includes flexing or compressing the strip of material along creases or the like to enable the strip of material to fit within the cavity. Thereafter, the strip of material is permitted to resiliently flex or expand outwardly into engagement with both the inner and masonry walls to form a debris collection surface that bridges the inner and masonry walls above the bottom surface of the wall cavity. As inserted, the strip of material preferably has an M-shaped or inverted U-shaped transverse cross-section.

According to another aspect of the present invention, a masonry cavity wall assembly is provided. The assembly includes a masonry wall, an adjacent inner wall, and a wall cavity extending therebetween above a base surface. An elongate strip of material is located within the wall cavity such that it is supported in a free-standing position on the base surface of the wall cavity. The strip of material provides a debris collection surface a spaced distance above the base surface for collecting excess

mortar and debris that falls within the wall cavity and for preventing the mortar and debris from clogging weep holes that are located adjacent the base surface of the cavity wall. The strip of material is an openwork material that permits moisture to drain therethrough and that prevents mortar from passing therethrough.

5 Preferably, the strip of material has opposite longitudinally-extending side sections, or legs, and a longitudinally-extending central section. One of the side sections extends upright and engages the masonry wall, while the other extends upright and engages the inner wall. The central section extends therebetween and forms the debris collection surface. Preferably, when located within the cavity, the
10 strip of material has an "M"-shaped or inverted "U"-shaped transverse cross-section.

BRIEF DESCRIPTION OF THE DRAWINGS

The features and advantages of the present invention should become apparent from the following description when taken in conjunction with the accompanying
15 drawings, in which:

FIG. 1 is a perspective view of a strip of material for use as a mortar and debris blocker according to the present invention;

FIG. 2 is a perspective view of the strip of material provided in a spiral roll;

FIG. 3 is a broken-away perspective view of a cavity wall assembly according
20 to the present invention;

FIG. 4 is a broken-away front elevational view of the cavity wall assembly;

FIG. 5 is a cross-sectional view taken along line 5--5 of FIG. 3;

FIG. 6 is a perspective view of an alternate strip of material for use as a mortar and debris blocker according to the present invention;

25 FIG. 7 is a transverse cross-section view of the strip of material of FIG. 6;

FIG. 8 is a broken-away perspective view of another cavity wall assembly according to the present invention; and

FIG. 9 is a cross-sectional view taken along line 8--8 of FIG. 8.

DETAILED DESCRIPTION OF THE INVENTION

A mortar and debris blocker according to the present invention is made of an elongate strip of openwork material that is sufficiently dense to support mortar and other construction debris thereon and that has sufficient openings therein to permit
5 liquid, moisture vapor, and air to flow, or drain, therethrough. Thus, the blocker can be used in cavity wall construction to prevent mortar and other construction debris that may fall within a wall cavity from clogging or restricting flow through weep or ventilation openings typically located at the base of such walls. The openings in the material permit water to drain through the blocker to weep holes and permit air flow
10 for evaporation of any moisture accumulated within the wall.

In an first embodiment of the present invention illustrated in FIGs. 1-5, the blocker 10 is provided as a relatively-flat strip of material having a width "W1" (as measured in a flat condition) greater than a width "W2" of the wall cavity in which it is to be installed. The strip of material 10 is sufficiently flexible at least along a
15 longitudinally-extending central section 12 thereof to permit the normally flat strip 10 to be inserted within the cavity in a bowed or inverted U-shape across its width. Thus, a pair of longitudinally-extending side sections, 14 and 16, of the strip 10 engage opposed wall surfaces that define the cavity, and the longitudinally-extending central section 12 forms an upwardly-projecting, debris-collection canopy therebetween that
20 bridges the opposed walls.

The blocker 10 possesses a degree of resiliency such that, when flexed or folded along its longitudinally-extending central section 12, the strip exerts a force to expand to its normal relatively-flat condition. In this way, when flexed and positioned within a wall cavity, the strip 10 automatically expands into engagement with the
25 opposed wall surfaces defining the cavity to ensure that the blocker engages the opposed walls and bridges across the entire width of the cavity throughout the length of the blocker.

A specific example of an openwork material for the blocker 10 is a porous, closed-cell composite 10 as illustrated in FIGs. 1 and 2 in which closed cell polymer
30 beads are fused together along contacting surfaces thereof. A network of openings

extend adjacent non-contacting surfaces of the beads and permit fluids to flow through the composite. The beads can be made, for instance, of polypropylene, polyethylene or like materials. Alternatively, a mat of fibers (not shown), a metal or plastic screen (not shown) or like openwork material can be utilized.

5 By way of example, and not be way of limitation, the blocker 10 can be provided in strips of any length and is preferably stored and shipped in a spiral roll 18 as illustrated in FIG. 2. The strip 10 can have a width "W1" of about 4 inches to about 16 inches, or more and can have a thickness "T" of about 0.125 inch to about 2 inches, or more.

10 As shown in FIGs. 3-5, a cavity wall assembly 20 includes an inner wall 22 that can be made of wood sheathing, OSB, brick, concrete or like material and that may be covered with housewrap, building paper, felt, insulation or like materials. The assembly also includes an outer wall 24 that is typically made of brick, cement block, stone or like material held together with mortar or the like. The inner and outer walls,
15 22 and 24, are typically vertical and extend in a parallel, spaced-apart relation such that a cavity 26 is formed therebetween. The cavity 26 typically has a width "W2" of about 2 inches to about 4 inches, but may be greater. Weep holes or like drainage and/or ventilation openings 28 are typically provided through the outer wall 24 adjacent the bottom 30 of the cavity 26 to provide drainage paths (see arrows in FIG.
20 5) for any moisture that may enter the cavity 26.

 A continuous length of the blocker 10 is positioned in a free-standing condition on the bottom 30 of the cavity 26 in an upwardly-bowed, or inverted U-shaped, configuration. In this position, the blocker 10 provides an upwardly-projecting canopy 32 that extends to an elevation above the weep holes 28 and that
25 prevents excess mortar and like debris from reaching the location of the weep holes 28. As best illustrated in FIG. 5, the longitudinally-extending side section 14 of the blocker 10 engages the inner wall 22, the longitudinally-extending side section 16 of the blocker 10 engages the outer wall 24, and the longitudinally-extending central section 12 of the blocker 10 is flexed in a bowed configuration therebetween forming
30 the upwardly-projecting canopy 32. As illustrated, preferably side edges, 34 and 36,

of the blocker 10 engage the bottom 30 of the cavity 26, and the side sections, 14 and 16, confront and extend parallel to the walls 22 and 24 for a given height "H". This ensures that the central section 12 of the blocker 10 is positioned and supported above the weep holes 28 and bottom 30 of the cavity 26 and reinforces the canopy structure.

5 During assembly of the cavity wall 20, the inner wall 22 and a base portion 38 of the outer wall 24 are constructed. The base portion 38 can include, for instance, the lowermost course or lowermost several courses of bricks or the like which is of a height enabling the blocker 10 to be readily positioned by hand in the bottom 28 of the cavity 26. A continuous, elongate strip of blocker 10 is inserted within the cavity 26
10 to form an upwardly-projecting, hollow canopy 32 therein. The strip 10 can be of a length equal to the length of the cavity 26, and the method of assembly can include providing an elongate strip of blocker 10 in a spiral roll 18, unrolling the blocker 10, and cutting it to the length of the cavity 26.

Preferably, the step of inserting the blocker 10 in the cavity 26 is accomplished
15 by flexing, or folding, the relatively flat strip of blocker 10 along its longitudinally-extending central section 12 so that the blocker 10 fits within the cavity 26. Thereafter, the blocker 10 is permitted to flex into engagement with the inner wall 22 and outer wall 24 due to its resilient nature. Thus, an upwardly projecting canopy 32 is formed in the cavity and extends the length of the cavity. Thereafter, the cavity
20 wall assembly 20 is completed by constructing an upper section 40 of the outer masonry wall 24. Any excess mortar 42 falling into the cavity 26 falls on and is supported by the canopy 32.

FIGs. 6-9 illustrate a second embodiment of the present invention. The blocker 50 is provided as an elongate strip of material 52 that can be folded, bent, or
25 flexed into an "M" shape in transverse cross section (see FIG. 7). Preferably, the material 52 has three longitudinally-extending creases, or fold lines, 54, 56 and 58, permitting the sheet of material 52 to be folded, bent or flexed into the M-shape. The legs 60 and 62 of the M-shaped blocker 50 can be engaged with the opposed wall surfaces of a wall cavity, and a central section 64 of the M-shaped blocker provides a
30 debris collection surface, or trough, that bridges the opposed walls.

Preferably, the blocker 50 possesses a degree of resiliency such that, when flexed or folded along its creases, 54, 56 and/or 58, into a compressed M-shape, the blocker 50 exerts a force to expand outwardly in an accordion manner. For example, see the dashed lines illustrated in FIG. 7 showing the blocker in an expanded condition. In this way, when compressed and positioned within a wall cavity, the M-shaped blocker 50 automatically expands into engagement with the opposed wall surfaces defining the cavity to ensure that the blocker engages the opposed walls and bridges across the entire width of the cavity throughout the length of the blocker. Alternatively, the blocker 50 can be manually expanded and/or compressed into a desired width.

The openwork material 52 for the blocker 50 can be perforated sheet metal, a perforated polymer sheet, a stiff porous foam, a mat of fibers, or the like. By way of example, and not by way of limitation, the material 52 can be a perforated sheet of aluminum that is 4 feet in length by 3 feet in width and that has three serrated fold lines formed along its length. The fold lines can also be formed at desired radius of curvatures to permit ready flexing, or hinging, of the material along the fold lines. The legs 60 and 62 can extend to a height "A" of about 10 inches, and the spacing "B" between creases 54 and 56, and 56 and 58, can be about 8 inches.

As shown in FIGs. 8 and 9, a cavity wall assembly 66 includes an inner wall 68 that can be made of wood sheathing, OSB, brick, concrete or like material and that may be covered with housewrap, building paper, felt, insulation or like materials. The assembly also includes an outer wall 70 that is typically made of brick, cement block, stone or like material held together with mortar or the like. The inner and outer walls, 68 and 70, are typically vertical and extend in a parallel, spaced-apart relation such that a cavity 72 is formed therebetween. The cavity 72 typically has a width of about two inches to about four inches, but may be greater. Weep holes or like drainage and/or ventilation openings 74 are typically provided through the outer wall 70 adjacent the bottom 76 of the cavity 72 to provide drainage paths for any moisture that may enter the cavity.

A continuous length of the M-shaped blocker 50 is positioned in a free-standing condition on the bottom 76 of the cavity 72. In this position, the blocker 50 provides a debris collection surface 64 that extends at an elevation above the weep holes 74 and that prevents excess mortar and like debris from reaching the weep holes 74. As best illustrated in FIG. 9, the longitudinally-extending side section, or leg, 60 of the blocker 50 engages the inner wall 68, the longitudinally-extending side section, or leg, 62 of the blocker 50 engages the outer wall 70, and the longitudinally-extending central section 64 of the blocker 50 provides a debris and mortar collection trough therebetween. The longitudinal-extending edges, or feet, 78 and 80, of the blocker 50 engage the bottom 76 of the cavity 72 in a free-standing manner, and the legs, 60 and 62, confront and extend parallel to the walls 68 and 70. This ensures that the central section 64 of the blocker 50 is positioned and supported above the weep holes 74 and bottom 76 of the cavity 72.

During assembly of the cavity wall 66, the inner wall 68 and a base portion 82 of the outer wall 70 are constructed. The base portion 82 can include, for instance, the lowermost course or lowermost several courses of bricks or the like which is of a height enabling the blocker 50 to be readily positioned by hand in the bottom 76 of the cavity 72. A continuous, elongate strip of blocker 50 is inserted within the cavity 72 to form a debris collection surface 64. Preferably, the step of inserting the blocker 50 in the cavity 72 is accomplished by compressing the M-shaped blocker 50 in an accordion manner so that the blocker 50 easily fits within the cavity 72. Thereafter, the blocker 50 is manually or automatically expanded into engagement with the inner wall 68 and outer wall 70. Thus, a debris collection surface, or trough 64 can be formed in the cavity 72 throughout the length of the cavity. Thereafter, the cavity wall assembly 66 is completed by constructing an upper section 84 of the outer masonry wall 70. Any excess mortar 86 falling into the cavity 72 falls onto and is supported by the debris collection surface 64.

The above-described mortar and debris blockers are easy to install, inexpensive to manufacture, and provide the required mortar blocking function while permitting fluids to drain or flow therethrough.

While preferred blockers, assemblies and methods have been described in detail, various modifications, alterations, and changes may be made without departing from the spirit and scope of the blockers, assemblies and methods according to the present invention as defined in the appended claims.

What is claimed is:

1. A method of assembling a cavity wall with a debris blocker, comprising the steps of:

5 assembling a base section of a masonry wall adjacent an inner wall
such that a wall cavity is defined therebetween;
inserting an elongate strip of material within said wall cavity after said
base section assembling step so that said strip of material is
supported in a free-standing condition on a bottom surface of
10 said wall cavity and forms a debris collection surface a spaced
distance above said bottom surface of said wall cavity, said
material being an openwork material that permits moisture to
drain therethrough and prevents mortar from passing
therethrough; and
15 after said inserting step, completing assembly of an upper section of
said masonry wall such that any excess mortar falling into said
wall cavity falls on, and is supported by, said debris collection
surface.

20 2. A method according to claim 1, wherein said openwork material consists of
a single layer of a single material selected from a group consisting of a perforated
sheet of metal, a perforated polymer sheet, a sheet of porous foam, and a mat of fibers.

25 3. A method according to claim 2, wherein said elongate strip of material has
opposite longitudinally-extending side sections and a longitudinally-extending central
section, and wherein said inserting step includes positioning one of said side sections
in an upright position in engagement with said inner wall, positioning the other of said
side sections in an upright position in engagement with said masonry wall, and
permitting said central section to extend between upper ends of said side sections to
30 form said debris collection surface.

4. A method according to claim 3, wherein said inserting step includes placing a longitudinally-extending free edge of each of said side sections into engagement with said bottom surface of said wall cavity.

5 5. A method according to claim 4, wherein said inserting step includes flexing said strip of material along said longitudinally-extending central section so that said strip of material fits within said wall cavity and thereafter, permitting said strip of material to resiliently flex into engagement with said inner and masonry walls.

10 6. A method according to claim 4, further comprising the step of folding said strip of material along longitudinally extending creases, before said inserting step, so that said strip of material is substantially "M"-shaped in transverse cross-section.

15 7. A method according to claim 6, wherein, during said inserting step, said "M"-shaped strip of material is compressed in an accordion manner so that said strip of material fits within said wall cavity, and thereafter, is expanded into engagement with said inner and masonry walls.

20 8. A method according to claim 1, wherein said strip of material has a substantially "M"-shaped transverse cross-section as positioned within said wall cavity.

25 9. A method according to claim 1, wherein said strip of material has a substantially inverted "U"-shaped transverse cross-section as positioned within said wall cavity.

10. A masonry cavity wall assembly, comprising:
an exterior masonry wall adjacent an inner wall defining a wall cavity
therebetween above a base surface; and

30

a free-standing elongate strip of material supported on said base surface within said wall cavity forming a debris collection surface a spaced distance above said base surface for supporting thereon excess mortar and debris falling within said wall cavity;
5 said strip of material being an openwork material that permits moisture to drain therethrough and prevents mortar from passing therethrough.

11. A masonry cavity wall assembly according to claim 10, wherein said strip
10 of material has a substantially "M"-shaped transverse cross-section.

12. A masonry cavity wall assembly according to claim 10, wherein said strip of material has a substantially inverted "U"-shaped transverse cross-section.

13. A masonry cavity wall assembly according to claim 10, wherein said strip
15 of material has a pair of longitudinally-extending substantially-upright side sections and a longitudinally-extending central section, and wherein one of said side sections engages said masonry wall, the other of said side section engages said inner wall, and said central section extends therebetween forming said debris collection surface.

20 14. A masonry cavity wall assembly according to claim 13, wherein said strip of material has three longitudinally-extending creases enabling said strip of material to have an M-shaped transverse cross section as inserted within said cavity.

25 15. A masonry cavity wall assembly according to claim 13, wherein said strip of material is compressible so that it can be positioned within said wall cavity in a compressed condition and is resilient so that it can resiliently expand into engagement with said inner and masonry walls.

30

16. A masonry cavity wall assembly according to claim 15, wherein said strip of material has an inverted U-shaped transverse cross section as inserted within said cavity.

5 17. A masonry cavity wall assembly according to claim 10, wherein said strip of openwork material is a perforated sheet of metal, a perforated sheet of polymer, or a rigid porous foam material.

10 18. A masonry cavity wall assembly according to claim 10, wherein said strip of material is a porous closed cell composite or a mat of fibers.

19. A masonry cavity wall assembly according to claim 10, wherein said strip of openwork material consists of a single layer of a single material.

15 20. A mortar and debris blocker, comprising a self-standing, elongate strip of material having an M-shape in transverse cross-section, said material consisting of a single layer of a perforated sheet of metal, a perforated sheet of polymer, or a rigid porous foam that permits moisture to drain therethrough and that prevents mortar from passing therethrough, said M-shaped strip of material being compressible and
20 expandable in an accordion manner to adjust its width.

1/5





FIG.3





FIG.4



3/5




FIG. 5





FIG. 7

Isidoro A. Infante
PATENT AGENTS

